# Neo E1100





# Tomorrow has come to light.

### **Highlights**

Memorable illuminated design with "breathing" lightpipe Glowing 2.2" QVGA display "Hidden" external OLED display Bluetooth 2.0 Speaker-independent voice recognition 1.3 MP camera with dedicated side key

#### **Additional Features**

Picture caller ID
MMS, EMS, SMS and instant messaging\*
Built-in MP3 ring tones, screen savers and wallpapers
Predictive text-input software for rapid text entry
Vibrate alert
Speakerphone
Micro-USB connector
2.5 mm mono headset jack
BREW® 3.1.5 technology\*
Web access and the ability to send and receive email\*
Supports multiple languages\*

# **Technical Specifications**

## Chipset

QSC6055

#### **Banding**

1xRTT, tri-band (800, 1900 MHz, AWS), S-GPS\*

#### Siz

89.5 x 52.0 x 16.7 mm

#### Weight

90g

#### **Screen Resolution**

Main: 2.2", 240 x 320 pixels, 262K- color QVGA

External: 16 x 104 pixels; single-color OLED

#### Battery Type 790 mAh Lilon

#### **Accessories**

Spare battery 790 mAh Travel charger Vehicle power charger Headset Bluetooth headset Strap

\*Depending on services available from your carrier.







Visit our Web site at www.kyocera-wireless.com Kyocera Wireless Corp., 10300 Campus Point Drive, San Diego, CA 92121 USA 1-800-349-4188, Outside USA 1-858-882-1410

©2008 Kyocera Wireless Corp., San Diego California, USA. All rights reserved. No reproduction in whole or in part is allowed without prior written approval. Kyocera is a registered trademark of Kyocera Corporation. The Genuine Accessories by Kyocera logo is a trademark of Kyocera Wireless Corp. CDMA2000 is a registered trademark of TIA USA. All other marks are held by their respective owners.

Features and specifications are subject to change without notice. Non-metric weights and measures are approximate. Not all products may be available in your area.